

Cable tray crossarm specifications and spacing



Overview

The drawings which constitute a part of these specifications indicate the general route of the cable tray systems.

Key Takeaways

Cable tray crossarms are typically U- or L-shaped galvanized steel supports with thicknesses of 2.5–4mm, spaced 500–1000mm apart depending on load requirements.

Material and Construction

Cable tray crossarms are generally made from Q235 low-carbon steel and are formed via rolling. Their cross-sectional shapes are usually U-shaped or L-shaped, providing structural rigidity while supporting cable trays effectively. The crossarms are hot-dip galvanized to resist corrosion, with a final passivation (chromate treatment) to seal the zinc coating and ensure long-term durability.

Dimensions and Thickness

Thickness: 2.5mm, 3mm, or 4mm, selected based on the expected load. Length: Matches the width of the cable tray, commonly 300mm, 400mm, or 500mm.

Flange width: For heavy-load applications, the flange width may be increased to 60–80mm to enhance stiffness. Load Capacity Light-duty trays (control cables): design load ~50 N/m. Power cable trays: 150–200 N/m.



Heavy-duty scenarios (e.g., metallurgical workshops): >300 N/m, requiring stiffened crossarm structures.

Spacing and Deflection

Crossarms are typically spaced 500–1000mm apart, forming support nodes for the cable tray.

According to G

B 50217 Code for Design of Cables in Electric Power Engineering, the maximum deflection of a crossarm should not exceed $L/200$, where L is the support spacing. For example, a 1000mm spacing allows a maximum sag of 5mm.

Installation Notes

Crossarms are fixed to cable tray connectors using bolts. The spacing and thickness should be selected based on the type of cables, tray width, and environmental conditions. For small-diameter control and instrumentation cables, closer spacing (e.g., 500mm) is recommended to prevent drooping.

For large power cables, wider spacing may be acceptable, but the crossarm must meet the required load and deflection limits. By following these specifications, cable tray systems can maintain structural integrity, prevent excessive sag, and ensure safe and reliable cable support in industrial and commercial installations.

Article Content

Full cable tray systems specification document

The drawings which constitute a part of these specifications indicate the general route of the cable tray systems. Data presented on these drawings is as accurate as preliminary surveys and planning can

Cable Tray Technical Guide A practical guide to product selection and ...

As per the NEC, the maximum allowable rung spacing is 9 inches (230 mm) when cable tray carries sin-gle-conductor cables of 1/0 to 4/0 AWG (American Wire Gauge) (Appendix I).

GUIDE CABLE TRAYS TECHNICAL

NEMA VE 1-2017 Specifies requirements for metal cable trays and associated fittings designed for use in accordance with the rules of Canadian Electrical Code, Part I and the National Electrical Code®

Trapezoidal cable tray crossarm spacing

The spacing between trays, whether horizontal or vertical, depends on various factors like cable type, environment, and tray material. Proper installation can significantly reduce electromagnetic

Cable Tray Spacing Standards for Installation and Safety

Discover the essential cable tray spacing requirements for safe and efficient installation. Learn key standards, horizontal and vertical spacing, and more.

B-Line series Cable Tray Design Considerations

Ladder cable tray is available in widths of 6, 9, 12, 18, 24, 30, 36, 42 and 48 inches with rung spacings of 6, 9, 12 or 18 inches. Note that wider rung spacings and wider cable tray widths decrease the overall

Cable Tray Support Spacing: Key Guidelines Explained

Explore the essential cable tray support spacing requirements for safe and efficient installations. Learn NEC guidelines for perforated, ladder, and wire

Cable Tray Design and Standards Guide

The document outlines codes and standards that must be followed for design and construction of cable trays and their components. Standards listed include those for materials, rolling and cutting

Galvanized Crossarms for Cable Trays: Analysis of Functions,

The standard length matches the width of the cable tray, with common specifications including 300mm, 400mm, and 500mm. They are fixed to the connectors on the side of the cable tray using bolts,

NEMA BI 50016-2024

425 wire mesh cable tray fitting: A fitting for wire mesh cable tray systems that is fabricated from wire mesh 426 cable tray straight sections. The fitting is field-constructed and attached to the adjacent

Cable Tray Technical Guide A practical guide to product selection and ...

Cable Tray Technical Guide A practical guide to product selection and installation This guide for engineers and installers has been developed by ABB as a practical reference regarding cable tray

B-Line series Cable Tray Design Considerations

Is your cable tray system optimized for safety, dependability, space and cost savings? Cable tray (or cable ladder) systems are a popular alternative to electrical conduit systems, as they have an

KwikRail cable tray specification Document

Cable tray systems are defined to include, but are not limited to straight sections of of [ladder type] [vented bottom type] [solid bottom type] cable trays, bends, tees, elbows, drop-outs, supports, and

Best Practice Guide to Cable Ladder and Cable Tray Systems

These guidelines will be particularly useful for the design, specification, procurement, installation and maintenance of these systems. Cable ladder systems and cable tray systems are designed for use

26 05 36 Cable Trays for Electrical Systems

EATON B-LINE SERIES GUIDE SPECIFICATION Section 26 05 36 – CABLE TRAYS FOR ELECTRICAL SYSTEMS 26 05 364/2025 Specifier Notes: This product guide specification is written

Guide to cable support systems

The systems allow large sup-port spacings of wide span systems or the multilayer arrangement of cable trays and cable ladder systems. The systems comprise I hanging supports, support brackets, head

Full cable tray systems specification document

B. Cable tray systems are defined to include, but are not limited to straight sections of [ladder type] [trough type] [solid bottom type] [channel type] cable trays, bends, tees, elbows, drop-outs, supports

12-SDMS-06

Cable tray supports shall have a maximum of 6 m spacing on horizontal run and 2.4 m spacing on the vertical runs. However, when the tray system is supported from building structure with rods, brackets

Contact Us

Continue your research online:

Website: <https://cgweb.co.za>

Technical inquiry: <https://cgweb.co.za/project-enquiry.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

