Core Switch Time Synchronization

Overview

Design of Time-Synchronized Switch Based on Zynq To meet the demands for high precision, high flexibility, and broad applicability, a switch with WR functi.

Key Takeaways

Core switches use NTP to synchronize system time across the network, ensuring accurate timestamps, security, and operational consistency. Overview of Time Synchronization on Core SwitchesCore switches typically synchronize their clocks using Network Time Protocol (NTP), often sourcing time from a GPS or external NTP server. Accurate time is critical for logging, authentication, auditing, and coordination of network events.

Both IPv4 and IPv6 NTP servers are supported, and it is recommended to configure NTP before enabling secure management protocols.

Configuring NT

P on Core SwitchesEnable NTP and Authentication: Configure NTP on the switch and enable authentication to ensure secure time updates. For example, using MD5 keys: CodeCopyswitch# ntp authentication-key 1 md5 switch# ntp authenticateswitch# ntp server 10. 100.

1. 254 key 1 This ensures the switch only accepts time updates from trusted sources. Redundancy: For high availability, configure multiple NTP servers.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Core switches can act as NTP sources for downstream devices, including Windows servers. Windows clients can be configured with multiple NTP peers to automatically switch if one server fails: CodeCopyw32tm /config /manualpeerlist:"IP_of_Core_Switch_A, IP_of_Core_Switch_B" /syncfromflags:manual /reliable:yes /updatew32tm /resync This setup provides redundancy and prevents time drift if one switch becomes unreachable.

Management I

P vs Loopback: Use a reachable IP address (management or loopback) for NTP configuration. Loopback addresses are preferred for stability, as they remain reachable even if a physical interface goes down.

Windows Time Service Integration

Windows servers use the W32Time service to synchronize with NTP servers. By default, domain-joined computers sync through the Active Directory hierarchy, but they can be manually configured to use core switches as NTP sources.

W32

Time communicates over UDP port 123, which must be open on firewalls between the server and the switch.

Verification and Troubleshooting

On switches, use commands like show ntp status and show ntp associations to verify synchronization and server reachability. On Windows servers, use w32tm /query /status to check the current time source and synchronization state. Common issues include firewall restrictions, incorrect NTP server IPs, high clock drift, or misconfigured NTP peering.

Best Practices

Set all devices to UTC to simplify multi-timezone management.

Enable NT

P authentication to prevent malicious time updates. Regularly monitor NTP status to detect drift or synchronization failures. Use multiple NTP servers for redundancy and reliability.

By following these practices, core switches can provide a stable and secure time synchronization service across the network, supporting both network devices and Windows servers.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Article Content

Design of Time-Synchronized Switch Based on Zynq

To meet the demands for high precision, high flexibility, and broad applicability, a switch with WR functionality has been designed based on the Zynq platform.

Timing and Synchronization Configuration Guide, Cisco Catalyst

Manufacturing zone synchronization: Core switches and devices in the Manufacturing Zone obtain time from the NTP Time Mirror in the DMZ. Core switches distribute NTP time to manufacturing devices.

NTP Sync for Windows Servers from Cisco Core Switch A and B

Solved: Hi, We want to sync NTP for windows server from core switch. We have core switch A and B and both are connected via fiber and have individual management address and

Configuring NTP to Synchronize Time

On the data center network, manually setting system time on all devices is time-consuming and the system time may be inaccurate. The NTP protocol can quickly synchronize

AM65xx Time Synchronization Architecture

Figure 2 shows a functional view of the time sync network in the AM65xx device, where sync signals from each protocol interfaces are interconnected via the Time Sync network.

How to Synchronize the Timing Between Chips With Programmable

This application note describes how to use IEP timer and PRU cores to perform time synchronization between chips and transmitting data with configurable timing under control cycle via Fast Serial

Ethernet TSN (Time Sensitive Networking) Switch IP Core (TSN-SW)

A configurable number of 2 to 24 full-duplex Ethernet ports plus one internal port are available. The design implements a 1GbE switching bar with cut-through capability at wire speed. It provides time

Time Synchronization

One of the most commonly-used protocols to accomplish this is the Network Time Protocol (NTP), which can use both local and Internet-hosted servers to synchronize system time across a network.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Ethernet IP Core

TSN IP cores enable real-time, deterministic Ethernet communication for advanced driver-assistance systems (ADAS), in-vehicle networking, and autonomous driving, ensuring synchronized data

Multiport Time Sensitive Networking Switch Core

MTSN is a multi-port, multi-rate managed Ethernet switch with Time-Sensitive Networking (TSN) capabilities to achieve deterministic Ethernet solutions in which streams are delivered with

Azure OpenAI Service Multitenant Load Balancing and Token Per

This example shows how a multitenant service can distribute requests evenly among multiple Azure OpenAI Service instances and manage tokens per minute (TPM)...

Clock and Timing Systems

We provide the broadest portfolio of clock and timing systems in the industry. Our state-of-the-art solutions are based on our long heritage in the field of

5G synchronization requirements and solutions

Network synchronization is key to optimal radio network performance. While there is no change to fundamental synchronization requirements in the move from 4G to 5G, wider use of TDD

Configure System Time Settings on a Switch through the Command ...

This article provides instructions on how to configure the system time settings on Sx300, Sx350, SG350X, Sx500, Sx550X series switches through the Command Line Interface (CLI).

Configuring Time Synchronization on AOS-S Switches

Configuring Time Synchronization on AOS-S Switches Time synchronization in a switch ensures maintaining a uniform time among all interoperating devices. Classic Central offers the following time

Sub-nanosecond Network Synchronisation

Challenge of Accurate Time Synchronisation f synchronisation of the slave to the master clock is described below. Here the two clocks are physically separated and so ther The two clocks are ticking

Timing and Synchronization Configuration Guide, Cisco IOS XE 16 (Cisco ...

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

If the packet contains a matching authentication key, the time-stamp information that is contained within the packet is accepted by the receiving client. NTP synchronization packets that do

Use Best Practices for Network Time Protocol

Core routers have a client/server relationship with external time sources, the internal time servers have a client/server relationship with the core routers, the internal user (non-time servers)

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://cgweb.co.za
Technical inquiry: https://cgweb.co.za/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved