

How to configure dual-link optical ports on a switch



Overview

Configuring Fibre Channel Interfaces This feature allows multiple applications on the N port to use different identifiers and allows access control, zoning.

Key Takeaways

Dual-link optical ports can be connected using compatible SFP/SFP+ transceivers and fiber cables, with the switch managing redundancy or failover between the links.

Physical Connection

To connect dual-link optical ports, you need matching SFP or SFP+ transceivers for each port on the switch. Ensure that both transceivers support the same speed (e.g., 1 Gbps or 10 Gbps) and fiber type (single-mode or multi-mode) to avoid compatibility issues. Use LC-terminated fiber optic cables to connect the transceivers, ensuring that the transmit (TX) of one end connects to the receive (RX) of the other.

Pre-terminated fiber cables are recommended for ease of installation and minimal signal loss.

Redundancy and Failover

Many switches, such as ExtremeSwitching or Summit models, support automatic failover between copper and fiber or between multiple fiber links on combination ports. When connecting dual optical links: Connect each fiber to a separate SFP port on the switch. The switch will typically activate one link as primary and the other as redundant.

If the active link fails, the switch automatically switches to the backup link without manual intervention. The order in which connectors are inserted can determine which link is active. For example, if a copper port is connected first, it may be treated as active, and the fiber port as redundant.

Inserting the fiber first can reverse this behavior.

Configuration Considerations

Verify SF

P compatibility with your switch using the manufacturer's optics-to-device compatibility matrix or commands like `show idprom interface`. Ensure both links are configured for the same speed and duplex settings to prevent link negotiation issues. For dual-link setups intended to increase bandwidth rather than redundancy, consider link aggregation (LACP) if supported by your switch, which allows multiple fiber links to operate as a single logical connection.

Best Practices

Use multi-mode fiber (OM3/OM4) for short distances and single-mode fiber (OS2) for longer runs. Avoid bending fiber cables sharply; maintain proper bend radius to prevent signal loss or damage. Label each fiber and transceiver to simplify troubleshooting and maintenance.

Test each link individually before enabling redundancy or aggregation to ensure proper operation. By following these steps, you can safely connect dual-link optical ports on a switch, achieving either redundancy or increased bandwidth while maintaining network stability and performance.

Article Content

Configuring Fibre Channel Interfaces

This feature allows multiple applications on the N port to use different identifiers and allows access control, zoning, and port security to be implemented at the application level.

Configuring Fibre Channel Interfaces

Each physical Fibre Channel interface in a switch may operate in one of several port modes: E mode, TE mode, F mode, and SD mode (see the figure below). A physical Fibre Channel interface can be

How to Connect Multiple Ethernet Switches Using Fiber Optic Cables ...

To connect multiple Ethernet switches, the best way is to use a multi-strand fiber cable. The 4-strand pre-terminated fiber optic cable consists of four individual strands or fibers of glass or

Typical CLI Configuration Examples for TP-Link JetStream Switch

The following configuration describes how to change the port duplex of SFP+ port 25 to Full mode. Note that TP-Link switches use Auto duplex mode by default and it is recommended to

Switch Ports

In order to enable and configure a mirrored port or range of ports, navigate to Switching > Monitor > Switch Ports. On this page select the ports that are intended for mirroring and hit the

ExtremeXOS® User Guide

ExtremeXOS allows you to specify the medium as copper or fiber when configuring ExtremeSwitching switches with combination ports. If the medium is not specified for combination ports then the

How to configure Optical Line Terminal (OLT) and Omada Switch with ...

Add the port connected to OLT as a tagged port (Here is port 9), and add the port connected to the IPTV as an untagged port (Here is port 4). Configure the corresponding PVIDs for

Understanding and Configuring Cisco Switch Ports: Best ...

Learn how to properly configure Cisco switch ports, understand port numbering (X/Y/Z), assign VLANs, enable PoE, and follow best practices to optimize enterprise network performance and stability.

Online Bulk Cable Company | CableWholesale

As a premier online bulk cable company, CableWholesale carries a large inventory of computer cables, USB, HDMI, fiber optic, VGA cables, and more. Shop now!

Fibre Channel

TE_Port (Trunking E_Port) A trunking expansion port that expands the functionality of E ports to support VSAN trunking, Transport quality of service (QoS) parameters, and Fibre Channel trace (fctrace)

Semiconductor & System Solutions | Infineon Technologies

Infineon Semiconductor & System Solutions - MCUs, sensors, automotive & power management ICs, memories, USB, Bluetooth, WiFi, LED drivers, radiation h

Cisco Catalyst 2960-S and 2960 Series Switches with LAN Lite

Read this data sheet to learn the benefits, specifications, and ordering information for the Cisco Catalyst 2960 C Series Switches with LAN Lite Software.

RAMPS 1.4

Design In RAMPS 1.4 the capacitors and resistors are now surface mount (SMD) components. This provided more space for more passive components, as well as headers. This does

Learn with Cisco

Explore limitless learning opportunities for skills development, industry-recognized certifications, and product training to help you and your organizations thrive in

Microsemi Products | Microchip Technology

Find the products and services originally offered by Microsemi or the equivalents now offered by Microchip. Microchip acquired Microsemi Corp in 2018.

Download Cisco Packet Tracer 9.0

Step 1 : Connect to the Cisco Networking Academy resource hub Step 2 : Log in with your Cisco account or configure SSO with your Google account Step 3 : Click on the Cisco Packet

How to link two Network Switch with fiber cables

One of the advantages of fiber optical cable is its fast speed. In this video, you will see how to link two network ports together to achieve 2G bandwidth between the switches.

Backbone network

Backbone networks create links that allow long-distance transmission, usually 10 to 100 miles, and in certain cases - up to 150 miles. This makes backbone network essential to providing long-haul

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: <https://cgweb.co.za>

Technical inquiry: <https://cgweb.co.za/project-enquiry.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

